

Equiptop Grinding Machines

MODEL :- UF-618M , YOM :- 2010



<u>Title</u>	<u>Description</u>	<u>Unit</u>	<u>UF-618M</u>
<u>General</u>	Standard Mag Chuck	mm	150x450
	Max Grinding Capacity (L x W)	mm	480x178
	Table to Spindle Center	mm	460
<u>Longitudinal</u>	Manual Travel	mm	510
	Hydraulic Traverse	mm	480
	Hydraulic Motor	Hp	1
<u>Cross Movement</u>	Cross Feed (Manual / Auto)	mm	195x180
	Hand Feed / Revolution	mm	5
	Hand Feed / Graduation	mm	0.02
	Continuous Cross Feed (60Hz)	mm/min	20~320
	Incremental Cross Feed	mm/min	0.5~10
	Cross Feed Motor	W	40
<u>Down Feed</u>	Rapid Feed (Slow Feed)	mm/min	230 (29)
	Hand Feed / Revolution	m/min / rpm	1
	Hand Feed / Graduation	-	0.005
<u>Spindle</u>	Grinding Wheel (Dia x Width x Bore)	mm	203x12.7x31.75
	Spindle Speed (60Hz)	rpm	3450
	Spindle Drive Motor	Hp	2.0

Tech Center

Plot No. 2301, Road-D, Kranti Gate,
Metoda GIDC Ta.: Lodhika,
Dist: Rajkot 360 021 Gujarat (INDIA)

Office: +91 2827 286060
sales@confidenceautomation.com
www.confidenceautomation.com